



GENERAL REQUIREMENTS FOR LANDSCAPE WORK AT USF

THIS GENERAL REQUIREMENTS APPLY TO ALL LANDSCAPE MATERIAL AND IRRIGATION SYSTEM INSTALLATION WORK ON USF CAMPUS COMPLETED UNDER ALL MINOR PROJECTS CONTRACTS OR PURCHASE ORDERS. THE CONTRACTOR SHALL ACKNOWLEDGE, SIGN AND ATTACH A COPY OF THIS AS AN ATTACHMENT TO PROPOSAL OR BID.

I

LANDSCAPE PLANTING REQUIREMENTS (CHECK ALL APPLICABLE LINES)

ONLY TO REMOVE DEAD OR BROKEN TWIGS; DO NOT PRUNE TO MODIFY SIZE OR SHAPE.			
ALL	FORM ROOT BALL & TREE; PEEL & REMOVE	FROM TOP OF ROOT BALL.	
	TO LOOSEN SOIL IN EXCAVATED	, ABOVE BOTTOM ELEVATION OF ROOT BALL	
PLANT TREE SO THAT ROOT FLARE IS VISIBLE:			
		; BOTTOM OF ROOT BALL SHALL REST ON EXISTING OR RE-COMPACTED SOIL.	
POSITION TREE IN A	LIGHTLY	AROUND ROOT BALL, THOROUGHLY	WITH WATER TO SETTLE SOIL AROUND ROOT
BALL AND			
INSTALL			

SECURE TREE WITH 1 1/2'

; WEBBING SHALL BE DARK GREEN OR BLACK COLOR. DO NOT USE HOSE AND WIRE.

TREE.

ATTACH WEBBING TO

(2" x 2